



ROLLER BALL LOCK TYPE CABLE TIES

UNCOATED



Technical Specifications

Material : 304 and 316L grade non-magnetic stainless steel
Temperature Range : -60°C to +300°C
Surface Finish : Metallic
Flamability Rating : UL94 Fireproof & UV Resistant

| Part Code as per Stainless Steel Grade | | Width | | Length | | Thickness | | Max. Loop Diameter | | Max Loop Tensile Strength | | Package Quantity |
|--|------------|-------|-----|--------|------|-----------|------|--------------------|-----|---------------------------|-----|------------------|
| SS304 | SS316L | Inch | mm | Inch | mm | Inch | mm | Inch | mm | N | lbs | Pcs |
| EBU14-100 | EBU16-100 | 0.18 | 4.6 | 4 | 100 | 0.01 | 0.25 | 0.94 | 24 | 667 | 150 | 100/bag |
| EBU14-127 | EBU16-127 | 0.18 | 4.6 | 5 | 127 | 0.01 | 0.25 | 1.02 | 26 | | | |
| EBU14-150 | EBU16-150 | 0.18 | 4.6 | 6 | 150 | 0.01 | 0.25 | 1.57 | 40 | | | |
| EBU14-200 | EBU16-200 | 0.18 | 4.6 | 8 | 200 | 0.01 | 0.25 | 2.20 | 56 | | | |
| EBU14-260 | EBU16-260 | 0.18 | 4.6 | 10 | 260 | 0.01 | 0.25 | 2.95 | 75 | | | |
| EBU14-300 | EBU16-300 | 0.18 | 4.6 | 12 | 300 | 0.01 | 0.25 | 3.46 | 88 | | | |
| EBU14-360 | EBU16-360 | 0.18 | 4.6 | 14 | 360 | 0.01 | 0.25 | 4.21 | 107 | | | |
| EBU14-400 | EBU16-400 | 0.18 | 4.6 | 16 | 400 | 0.01 | 0.25 | 4.53 | 115 | | | |
| EBU14-450 | EBU16-450 | 0.18 | 4.6 | 18 | 450 | 0.01 | 0.25 | 5.31 | 135 | | | |
| EBU14-520 | EBU16-520 | 0.18 | 4.6 | 20 | 520 | 0.01 | 0.25 | 6.22 | 158 | | | |
| EBU14-550 | EBU16-550 | 0.18 | 4.6 | 22 | 550 | 0.01 | 0.25 | 6.38 | 162 | | | |
| EBU14-620 | EBU16-620 | 0.18 | 4.6 | 24 | 620 | 0.01 | 0.25 | 7.48 | 190 | | | |
| EBU14-680 | EBU16-680 | 0.18 | 4.6 | 27 | 680 | 0.01 | 0.25 | 7.87 | 200 | | | |
| EBU14-840 | EBU16-840 | 0.18 | 4.6 | 33 | 840 | 0.01 | 0.25 | 10.24 | 260 | | | |
| EBU14-1000 | EBU16-1000 | 0.18 | 4.6 | 39 | 1000 | 0.01 | 0.25 | 12.24 | 311 | | | |

| Part Code as per Stainless Steel Grade | | Width | | Length | | Thickness | | Max. Loop Diameter | | Max Loop Tensile Strength | | Package Quantity |
|--|------------|-------|-----|--------|------|-----------|------|--------------------|-----|---------------------------|-----|------------------|
| SS304 | SS316L | Inch | mm | Inch | mm | Inch | mm | Inch | mm | N | lbs | Pcs |
| EBU24-100 | EBU26-100 | 0.31 | 7.9 | 4 | 100 | 0.01 | 0.25 | 0.94 | 24 | 1335 | 300 | 100/bag |
| EBU24-127 | EBU26-127 | 0.31 | 7.9 | 5 | 127 | 0.01 | 0.25 | 1.02 | 26 | | | |
| EBU24-150 | EBU26-150 | 0.31 | 7.9 | 6 | 150 | 0.01 | 0.25 | 1.57 | 40 | | | |
| EBU24-200 | EBU26-200 | 0.31 | 7.9 | 8 | 200 | 0.01 | 0.25 | 2.20 | 56 | | | |
| EBU24-260 | EBU26-260 | 0.31 | 7.9 | 10 | 260 | 0.01 | 0.25 | 2.95 | 75 | | | |
| EBU24-300 | EBU26-300 | 0.31 | 7.9 | 12 | 300 | 0.01 | 0.25 | 3.46 | 88 | | | |
| EBU24-360 | EBU26-360 | 0.31 | 7.9 | 14 | 360 | 0.01 | 0.25 | 4.21 | 107 | | | |
| EBU24-400 | EBU26-400 | 0.31 | 7.9 | 16 | 400 | 0.01 | 0.25 | 4.53 | 115 | | | |
| EBU24-450 | EBU26-450 | 0.31 | 7.9 | 18 | 450 | 0.01 | 0.25 | 5.31 | 135 | | | |
| EBU24-520 | EBU26-520 | 0.31 | 7.9 | 20 | 520 | 0.01 | 0.25 | 6.22 | 158 | | | |
| EBU24-550 | EBU26-550 | 0.31 | 7.9 | 22 | 550 | 0.01 | 0.25 | 6.38 | 162 | | | |
| EBU24-620 | EBU26-620 | 0.31 | 7.9 | 24 | 620 | 0.01 | 0.25 | 7.48 | 190 | | | |
| EBU24-680 | EBU26-680 | 0.31 | 7.9 | 27 | 680 | 0.01 | 0.25 | 7.87 | 200 | | | |
| EBU24-840 | EBU26-840 | 0.31 | 7.9 | 33 | 840 | 0.01 | 0.25 | 10.24 | 260 | | | |
| EBU24-1000 | EBU26-1000 | 0.31 | 7.9 | 39 | 1000 | 0.01 | 0.25 | 12.24 | 311 | | | |

| Part Code as per Stainless Steel Grade | | Width | | Length | | Thickness | | Max. Loop Diameter | | Max Loop Tensile Strength | | Package Quantity |
|--|------------|-------|----|--------|------|-----------|-----|--------------------|-----|---------------------------|-----|------------------|
| SS304 | SS316L | Inch | mm | Inch | mm | Inch | mm | Inch | mm | N | lbs | Pcs |
| EBU34-100 | EBU36-100 | 0.5 | 12 | 4 | 100 | 0.01 | 0.3 | 0.94 | 24 | 2000 | 450 | 100/bag |
| EBU34-127 | EBU36-127 | 0.5 | 12 | 5 | 127 | 0.01 | 0.3 | 1.02 | 26 | | | |
| EBU34-150 | EBU36-150 | 0.5 | 12 | 6 | 150 | 0.01 | 0.3 | 1.57 | 40 | | | |
| EBU34-200 | EBU36-200 | 0.5 | 12 | 8 | 200 | 0.01 | 0.3 | 2.20 | 56 | | | |
| EBU34-260 | EBU36-260 | 0.5 | 12 | 10 | 260 | 0.01 | 0.3 | 2.95 | 75 | | | |
| EBU34-300 | EBU36-300 | 0.5 | 12 | 12 | 300 | 0.01 | 0.3 | 3.46 | 88 | | | |
| EBU34-360 | EBU36-360 | 0.5 | 12 | 14 | 360 | 0.01 | 0.3 | 4.21 | 107 | | | |
| EBU34-400 | EBU36-400 | 0.5 | 12 | 16 | 400 | 0.01 | 0.3 | 4.53 | 115 | | | |
| EBU34-450 | EBU36-450 | 0.5 | 12 | 18 | 450 | 0.01 | 0.3 | 5.31 | 135 | | | |
| EBU34-520 | EBU36-520 | 0.5 | 12 | 20 | 520 | 0.01 | 0.3 | 6.22 | 158 | | | |
| EBU34-550 | EBU36-550 | 0.5 | 12 | 22 | 550 | 0.01 | 0.3 | 6.38 | 162 | | | |
| EBU34-620 | EBU36-620 | 0.5 | 12 | 24 | 620 | 0.01 | 0.3 | 7.48 | 190 | | | |
| EBU34-680 | EBU36-680 | 0.5 | 12 | 27 | 680 | 0.01 | 0.3 | 7.87 | 200 | | | |
| EBU34-840 | EBU36-840 | 0.5 | 12 | 33 | 840 | 0.01 | 0.3 | 10.24 | 260 | | | |
| EBU34-1000 | EBU36-1000 | 0.5 | 12 | 39 | 1000 | 0.01 | 0.3 | 12.24 | 311 | | | |