



ROLLER BALL LOCK TYPE CABLE TIES
COATED



Technical Specifications

- Material** : 304 and 316L grade non-magnetic stainless steel
- Temperature Range** : -60°C to +150°C
- Surface Finish** : Epoxy / Polyester Coated
- Flamability Rating** : UL94 Fireproof & UV Resistant

| Part Code as per Stainless Steel Grade | | Width | | Length | | Thickness | | Max. Loop Diameter | | Max Loop Tensile Strength | | Package Quantity |
|--|------------|-------|-----|--------|------|-----------|------|--------------------|-----|---------------------------|-----|------------------|
| SS304 | SS316L | Inch | mm | Inch | mm | Inch | mm | Inch | mm | N | lbs | Pcs |
| EBC14-100 | EBC16-100 | 0.18 | 4.6 | 4 | 100 | 0.01 | 0.25 | 0.94 | 24 | 465 | 105 | 100/bag |
| EBC14-127 | EBC16-127 | 0.18 | 4.6 | 5 | 127 | 0.01 | 0.25 | 1.02 | 26 | | | |
| EBC14-150 | EBC16-150 | 0.18 | 4.6 | 6 | 150 | 0.01 | 0.25 | 1.57 | 40 | | | |
| EBC14-200 | EBC16-200 | 0.18 | 4.6 | 8 | 200 | 0.01 | 0.25 | 2.20 | 56 | | | |
| EBC14-260 | EBC16-260 | 0.18 | 4.6 | 10 | 260 | 0.01 | 0.25 | 2.95 | 75 | | | |
| EBC14-300 | EBC16-300 | 0.18 | 4.6 | 12 | 300 | 0.01 | 0.25 | 3.46 | 88 | | | |
| EBC14-360 | EBC16-360 | 0.18 | 4.6 | 14 | 360 | 0.01 | 0.25 | 4.21 | 107 | | | |
| EBC14-400 | EBC16-400 | 0.18 | 4.6 | 16 | 400 | 0.01 | 0.25 | 4.53 | 115 | | | |
| EBC14-450 | EBC16-450 | 0.18 | 4.6 | 18 | 450 | 0.01 | 0.25 | 5.31 | 135 | | | |
| EBC14-520 | EBC16-520 | 0.18 | 4.6 | 20 | 520 | 0.01 | 0.25 | 6.22 | 158 | | | |
| EBC14-550 | EBC16-550 | 0.18 | 4.6 | 22 | 550 | 0.01 | 0.25 | 6.38 | 162 | | | |
| EBC14-620 | EBC16-620 | 0.18 | 4.6 | 24 | 620 | 0.01 | 0.25 | 7.48 | 190 | | | |
| EBC14-680 | EBC16-680 | 0.18 | 4.6 | 27 | 680 | 0.01 | 0.25 | 7.87 | 200 | | | |
| EBC14-840 | EBC16-840 | 0.18 | 4.6 | 33 | 840 | 0.01 | 0.25 | 10.24 | 260 | | | |
| EBC14-1000 | EBC16-1000 | 0.18 | 4.6 | 39 | 1000 | 0.01 | 0.25 | 12.24 | 311 | | | |

| Part Code as per Stainless Steel Grade | | Width | | Length | | Thickness | | Max. Loop Diameter | | Max Loop Tensile Strength | | Package Quantity |
|--|------------|-------|-----|--------|------|-----------|------|--------------------|-----|---------------------------|-----|------------------|
| SS304 | SS316L | Inch | mm | Inch | mm | Inch | mm | Inch | mm | N | lbs | Pcs |
| EBC24-150 | EBC26-150 | 0.31 | 7.9 | 6 | 150 | 0.01 | 0.25 | 1.57 | 40 | 1200 | 270 | 100/bag |
| EBC24-200 | EBC26-200 | 0.31 | 7.9 | 8 | 200 | 0.01 | 0.25 | 2.20 | 56 | | | |
| EBC24-260 | EBC26-260 | 0.31 | 7.9 | 10 | 260 | 0.01 | 0.25 | 2.95 | 75 | | | |
| EBC24-300 | EBC26-300 | 0.31 | 7.9 | 12 | 300 | 0.01 | 0.25 | 3.46 | 88 | | | |
| EBC24-360 | EBC26-360 | 0.31 | 7.9 | 14 | 360 | 0.01 | 0.25 | 4.21 | 107 | | | |
| EBC24-400 | EBC26-400 | 0.31 | 7.9 | 16 | 400 | 0.01 | 0.25 | 4.53 | 115 | | | |
| EBC24-450 | EBC26-450 | 0.31 | 7.9 | 18 | 450 | 0.01 | 0.25 | 5.31 | 135 | | | |
| EBC24-520 | EBC26-520 | 0.31 | 7.9 | 20 | 520 | 0.01 | 0.25 | 6.22 | 158 | | | |
| EBC24-550 | EBC26-550 | 0.31 | 7.9 | 22 | 550 | 0.01 | 0.25 | 6.38 | 162 | | | |
| EBC24-620 | EBC26-620 | 0.31 | 7.9 | 24 | 620 | 0.01 | 0.25 | 7.48 | 190 | | | |
| EBC24-680 | EBC26-680 | 0.31 | 7.9 | 27 | 680 | 0.01 | 0.25 | 7.87 | 200 | | | |
| EBC24-840 | EBC26-840 | 0.31 | 7.9 | 33 | 840 | 0.01 | 0.25 | 10.24 | 260 | | | |
| EBC24-1000 | EBC26-1000 | 0.31 | 7.9 | 39 | 1000 | 0.01 | 0.25 | 12.24 | 311 | | | |

| Part Code as per Stainless Steel Grade | | Width | | Length | | Thickness | | Max. Loop Diameter | | Max Loop Tensile Strength | | Package Quantity |
|--|------------|-------|----|--------|------|-----------|-----|--------------------|-----|---------------------------|-----|------------------|
| SS304 | SS316L | Inch | mm | Inch | mm | Inch | mm | Inch | mm | N | lbs | Pcs |
| EBC34-200 | EBC36-200 | 0.5 | 12 | 8 | 200 | 0.01 | 0.3 | 2.20 | 56 | 2000 | 450 | 100/bag |
| EBC34-260 | EBC36-260 | 0.5 | 12 | 10 | 260 | 0.01 | 0.3 | 2.95 | 75 | | | |
| EBC34-300 | EBC36-300 | 0.5 | 12 | 12 | 300 | 0.01 | 0.3 | 3.46 | 88 | | | |
| EBC34-360 | EBC36-360 | 0.5 | 12 | 14 | 360 | 0.01 | 0.3 | 4.21 | 107 | | | |
| EBC34-400 | EBC36-400 | 0.5 | 12 | 16 | 400 | 0.01 | 0.3 | 4.53 | 115 | | | |
| EBC34-450 | EBC36-450 | 0.5 | 12 | 18 | 450 | 0.01 | 0.3 | 5.31 | 135 | | | |
| EBC34-520 | EBC36-520 | 0.5 | 12 | 20 | 520 | 0.01 | 0.3 | 6.22 | 158 | | | |
| EBC34-550 | EBC36-550 | 0.5 | 12 | 22 | 550 | 0.01 | 0.3 | 6.38 | 162 | | | |
| EBC34-620 | EBC36-620 | 0.5 | 12 | 24 | 620 | 0.01 | 0.3 | 7.48 | 190 | | | |
| EBC34-680 | EBC36-680 | 0.5 | 12 | 27 | 680 | 0.01 | 0.3 | 7.87 | 200 | | | |
| EBC34-840 | EBC36-840 | 0.5 | 12 | 33 | 840 | 0.01 | 0.3 | 10.24 | 260 | | | |
| EBC34-1000 | EBC36-1000 | 0.5 | 12 | 39 | 1000 | 0.01 | 0.3 | 12.24 | 311 | | | |

❖ Also available in multicolor options.