



RELEASABLE TYPE CABLE TIES

PPA 571 COATED



Technical Specifications

Material	:	304 and 316L grade non-magnetic stainless steel
Temperature Range	:	-60°C to +90°C
Surface Finish	:	PPA 571 Black Coating
Flamability Rating	:	UL94 Fireproof & UV Resistant

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
ERC14-152	ERC16-152	1/4	6.35	6	152	0.015	0.40	1.5	38	1335	300	100/bag
ERC14-229	ERC16-229	1/4	6.35	9	229	0.015	0.40	2.5	63			
ERC14-305	ERC16-305	1/4	6.35	12	305	0.015	0.40	3.4	86			
ERC14-330	ERC16-330	1/4	6.35	13	330	0.015	0.40	3.7	95			
ERC14-457	ERC16-457	1/4	6.35	18	457	0.015	0.40	5.4	137			
ERC14-610	ERC16-610	1/4	6.35	24	610	0.015	0.40	7.3	185			
ERC14-762	ERC16-762	1/4	6.35	30	762	0.015	0.40	9.1	231			
ERC14-914	ERC16-914	1/4	6.35	36	914	0.015	0.40	11.0	280			
ERC14-1000	ERC16-1000	1/4	6.35	39	1000	0.015	0.40	11.8	300			
ERC14-1400	ERC16-1400	1/4	6.35	55	1400	0.015	0.40	16.9	430			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
ERC24-152	ERC26-152	3/8	9.53	6	152	0.015	0.40	1.5	38	1800	405	100/bag
ERC24-229	ERC26-229	3/8	9.53	9	229	0.015	0.40	2.5	63			
ERC24-305	ERC26-305	3/8	9.53	12	305	0.015	0.40	3.4	86			
ERC24-330	ERC26-330	3/8	9.53	13	330	0.015	0.40	3.7	95			
ERC24-457	ERC26-457	3/8	9.53	18	457	0.015	0.40	5.4	137			
ERC24-610	ERC26-610	3/8	9.53	24	610	0.015	0.40	7.3	185			
ERC24-762	ERC26-762	3/8	9.53	30	762	0.015	0.40	9.1	231			
ERC24-914	ERC26-914	3/8	9.53	36	914	0.015	0.40	11.0	280			
ERC24-1000	ERC26-1000	3/8	9.53	39	1000	0.015	0.40	11.8	300			
ERC24-1400	ERC26-1400	3/8	9.53	55	1400	0.015	0.40	16.9	430			

SALIENT FEATURES OF PPA 571 COATING

- ❖ PPA 571 is a flexible, tough and highly durable plastic coating.
- ❖ Superior resistance to Sun, Salt and Sea Water.
- ❖ Low temperature performance upto -60° C.
- ❖ Environment friendly, maintenance free, glossy attractive coating.
- ❖ Free of Bisphenol A (BPA), PVC, Halogens, Phthalates and Heavy metals.
- ❖ Smooth rounded edges.
- ❖ Flame retardant and Non-toxic.
- ❖ Water Absorption Free.