



LADDER TYPE CABLE TIES

UNCOATED



Technical Specifications

Material	: 304 and 316L grade non-magnetic stainless steel
Temperature Range	: -60°C to +300°C
Surface Finish	: Metallic
Flamability Rating	: UL94 Fireproof & UV Resistant

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
ELU14-100	ELU16-100	0.28	7	4	100	0.012	0.3	0.94	24	400	90	100/bag
ELU14-150	ELU16-150	0.28	7	6	150	0.012	0.3	1.89	48			
ELU14-200	ELU16-200	0.28	7	8	200	0.012	0.3	2.52	64			
ELU14-225	ELU16-225	0.28	7	9	225	0.012	0.3	2.83	72			
ELU14-250	ELU16-250	0.28	7	10	250	0.012	0.3	3.15	80			
ELU14-300	ELU16-300	0.28	7	12	300	0.012	0.3	3.78	96			
ELU14-350	ELU16-350	0.28	7	14	350	0.012	0.3	4.33	110			
ELU14-360	ELU16-360	0.28	7	14	360	0.012	0.3	4.53	115			
ELU14-400	ELU16-400	0.28	7	16	400	0.012	0.3	5.28	134			
ELU14-450	ELU16-450	0.28	7	18	450	0.012	0.3	5.63	143			
ELU14-500	ELU16-500	0.28	7	20	500	0.012	0.3	6.54	166			
ELU14-550	ELU16-550	0.28	7	22	550	0.012	0.3	7.13	181			
ELU14-610	ELU16-610	0.28	7	24	610	0.012	0.3	7.64	194			
ELU14-750	ELU16-750	0.28	7	30	750	0.012	0.3	9.41	239			
ELU14-1000	ELU16-1000	0.28	7	39	1000	0.012	0.3	12.52	318			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
ELU24-100	ELU26-100	0.47	12	4	100	0.012	0.3	0.94	24	800	180	100/bag
ELU24-150	ELU26-150			6	150	0.012	0.3	1.89	48			
ELU24-200	ELU26-200			8	200	0.012	0.3	2.52	64			
ELU24-225	ELU26-225			9	225	0.012	0.3	2.83	72			
ELU24-250	ELU26-250			10	250	0.012	0.3	3.15	80			
ELU24-300	ELU26-300			12	300	0.012	0.3	3.78	96			
ELU24-350	ELU26-350			14	350	0.012	0.3	4.33	110			
ELU24-360	ELU26-360			14	360	0.012	0.3	4.53	115			
ELU24-400	ELU26-400			16	400	0.012	0.3	5.28	134			
ELU24-450	ELU26-450			18	450	0.012	0.3	5.63	143			
ELU24-500	ELU26-500			20	500	0.012	0.3	6.54	166			
ELU24-550	ELU26-550			22	550	0.012	0.3	7.13	181			
ELU24-610	ELU26-610			24	610	0.012	0.3	7.64	194			
ELU24-750	ELU26-750			30	750	0.012	0.3	9.41	239			
ELU24-1000	ELU26-1000			39	1000	0.012	0.3	12.52	318			