




LADDER TYPE CABLE TIES

COATED

Technical Specifications

- Material** : 304 and 316L grade non-magnetic stainless steel
- Temperature Range** : -60°C to +150°C
- Surface Finish** : Pure Polyester Coating
- Flamability Rating** : UL94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
ELC14-100	ELC16-100	0.28	7	4	100	0.012	0.3	0.94	24	400	90	100/bag
ELC14-150	ELC16-150	0.28	7	6	150	0.012	0.3	1.89	48			
ELC14-200	ELC16-200	0.28	7	8	200	0.012	0.3	2.52	64			
ELC14-225	ELC16-225	0.28	7	9	225	0.012	0.3	2.83	72			
ELC14-250	ELC16-250	0.28	7	10	250	0.012	0.3	3.15	80			
ELC14-300	ELC16-300	0.28	7	12	300	0.012	0.3	3.78	96			
ELC14-350	ELC16-350	0.28	7	14	350	0.012	0.3	4.33	110			
ELC14-360	ELC16-360	0.28	7	14	360	0.012	0.3	4.53	115			
ELC14-400	ELC16-400	0.28	7	16	400	0.012	0.3	5.28	134			
ELC14-450	ELC16-450	0.28	7	18	450	0.012	0.3	5.63	143			
ELC14-500	ELC16-500	0.28	7	20	500	0.012	0.3	6.54	166			
ELC14-550	ELC16-550	0.28	7	22	550	0.012	0.3	7.13	181			
ELC14-610	ELC16-610	0.28	7	24	610	0.012	0.3	7.64	194			
ELC14-750	ELC16-750	0.28	7	30	750	0.012	0.3	9.41	239			
ELC14-1000	ELC16-1000	0.28	7	39	1000	0.012	0.3	12.52	318			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
ELC24-100	ELC26-100	0.47	12	4	100	0.012	0.3	0.94	24	800	180	100/bag
ELC24-150	ELC26-150	0.47	12	6	150	0.012	0.3	1.89	48			
ELC24-200	ELC26-200	0.47	12	8	200	0.012	0.3	2.52	64			
ELC24-225	ELC26-225	0.47	12	9	225	0.012	0.3	2.83	72			
ELC24-250	ELC26-250	0.47	12	10	250	0.012	0.3	3.15	80			
ELC24-300	ELC26-300	0.47	12	12	300	0.012	0.3	3.78	96			
ELC24-350	ELC26-350	0.47	12	14	350	0.012	0.3	4.33	110			
ELC24-360	ELC26-360	0.47	12	14	360	0.012	0.3	4.53	115			
ELC24-400	ELC26-400	0.47	12	16	400	0.012	0.3	5.28	134			
ELC24-450	ELC26-450	0.47	12	18	450	0.012	0.3	5.63	143			
ELC24-500	ELC26-500	0.47	12	20	500	0.012	0.3	6.54	166			
ELC24-550	ELC26-550	0.47	12	22	550	0.012	0.3	7.13	181			
ELC24-610	ELC26-610	0.47	12	24	610	0.012	0.3	7.64	194			
ELC24-750	ELC26-750	0.47	12	30	750	0.012	0.3	9.41	239			
ELC24-1000	ELC26-1000	0.47	12	39	1000	0.012	0.3	12.52	318			