



## STRAPS

### Technical Specifications

<b>Material</b>	: SS 201, SS 304 & SS 316
<b>Temperature Range</b>	: -60°C to +300°C (Uncoated) -60°C to +150°C (Coated)
<b>Surface Finish</b>	: Coated / Uncoated
<b>Flamability Rating</b>	: UL94 Fireproof & UV Resistant

Part Code as per Stainless Steel Grade			Width		Thickness		Finished Length		Average Breaking Strength						Package Quantity
SS201	SS304	SS316	Inch	mm	Inch	mm	feet	Mtrs	SS201		SS304		SS316		Pcs
									N	lbs	N	lbs	N	lbs	
ESU1-1X30	ESU4-1X30	ESU6-1X30	1/4	6.5	0.02	0.5	100	30.5	2225	500	1669	375	1780	400	100' / Roll
ESU1-2Y30	ESU4-2Y30	ESU6-2Y30	3/8	9.5	0.026	0.65	100	30.5	4005	900	3115	700	3338	750	100' / Roll
ESU1-3Z30	ESU4-3Z30	ESU6-3Z30	1/2	12.7	0.03	0.75	100	30.5	6675	1500	4895	1100	5340	1200	100' / Roll
ESU1-4Z30	ESU4-4Z30	ESU6-4Z30	5/8	16	0.03	0.75	100	30.5	8345	1875	6230	1400	6675	1500	100' / Roll
ESU1-5Z30	ESU4-5Z30	ESU6-5Z30	3/4	19	0.03	0.75	100	30.5	10015	2250	7365	1700	8010	1800	100' / Roll
-	ESP4-1X30	ESP6-1X30	1/4	6.5	0.02	0.5	100	30.5	-	-	1490	335	1490	335	100' / Roll
-	ESP4-2Y30	ESP6-2Y30	3/8	9.5	0.026	0.65	100	30.5	-	-	2250	505	2250	505	100' / Roll
-	ESP4-3Z30	ESP6-3Z30	1/2	12.7	0.03	0.75	100	30.5	-	-	2980	670	2980	670	100' / Roll
-	ESP4-4Z30	ESP6-4Z30	5/8	16	0.03	0.75	100	30.5	-	-	3740	840	3740	840	100' / Roll
-	ESP4-5Z30	ESP6-5Z30	3/4	19	0.03	0.75	100	30.5	-	-	4450	1000	4450	1000	100' / Roll

## NOMENCLATURE

**PRODUCT TYPE: ES/EA**

**SURFACE FINISH: U/C/P**

**MATERIAL GRADE: 1/4/6/G**

**WIDTH: 1/2/3/4/5**

**THICKNESS: X/Y/Z**

**STRAP LENGTH: xx**

**ES: STRAP**  
**EA: ALL PURPOSE BANDS**

**U: UNCOATED**  
**C: EPOXY/POLYESTER COATED**  
**P: PPA 571 COATED**

**1: SS 201 / 4: SS 304**  
**6: SS 316 / G: GCS**

**1: 6.5mm / 2: 9.5mm**  
**3: 12.7mm / 4: 16mm / 5: 19mm**

**X: 0.50mm / Y: 0.65mm**  
**Z: 0.75mm**

**xx: 3, 10, 25, 30.5, 50, 61**