



ALL PURPOSE BANDS

Technical Specifications

- Material** : SS 304, SS 316 & Galvanised Carbon Steel (GCS)
Temperature Range : -60°C to +300°C (Uncoated)
 : -60°C to +150°C (Coated)
Surface Finish : Coated / Uncoated
Flamability Rating : UL94 Fireproof & UV Resistant



UNCOATED

Part Code as per Stainless Steel Grade			Width		Thickness		Finished Length		Diameter of Hole		Package Quantity
GCS	SS304	SS316	Inch	mm	Inch	mm	feet	Mtrs	Inch	mm	Pcs
EAUG-3Z03	EAU4-3Z03	EAU6-3Z03	1/2	12.7	0.03	0.75	9.9	3	3/16	5	9.9' / Roll
EAUG-3Z10	EAU4-3Z10	EAU6-3Z10	1/2	12.7	0.03	0.75	33	10	3/16	5	33' / Roll
EAUG-3Z25	EAU4-3Z25	EAU6-3Z25	1/2	12.7	0.03	0.75	82.5	25	3/16	5	82.5' / Roll
EAUG-5Z03	EAU4-5Z03	EAU6-5Z03	3/4	19	0.03	0.75	9.9	3	9/32	7	9.9' / Roll
EAUG-5Z10	EAU4-5Z10	EAU6-5Z10	3/4	19	0.03	0.75	33	10	9/32	7	33' / Roll
EAUG-5Z25	EAU4-5Z25	EAU6-5Z25	3/4	19	0.03	0.75	82.5	25	9/32	7	82.5' / Roll



PPA 571 COATED

Part Code as per Stainless Steel Grade			Width		Thickness		Finished Length		Diameter of Hole		Package Quantity
GCS	SS304	SS316	Inch	mm	Inch	mm	feet	Mtrs	Inch	mm	Pcs
EAPG-3Z03	EAP4-3Z03	EAP6-3Z03	1/2	12.7	0.03	0.75	9.9	3	3/16	5	9.9' / Roll
EAPG-3Z10	EAP4-3Z10	EAP6-3Z10	1/2	12.7	0.03	0.75	33	10	3/16	5	33' / Roll
EAPG-3Z25	EAP4-3Z25	EAP6-3Z25	1/2	12.7	0.03	0.75	82.5	25	3/16	5	82.5' / Roll
EAPG-5Z03	EAP4-5Z03	EAP6-5Z03	3/4	19	0.03	0.75	9.9	3	9/32	7	9.9' / Roll
EAPG-5Z10	EAP4-5Z10	EAP6-5Z10	3/4	19	0.03	0.75	33	10	9/32	7	33' / Roll
EAPG-5Z25	EAP4-5Z25	EAP6-5Z25	3/4	19	0.03	0.75	82.5	25	9/32	7	82.5' / Roll