











## INTRODUCTION

Our product catalogue contains a wide range of cutting, crimping and other multipurpose hydraulic tools which are being generally used in the Electrical Industry. A brief technical write up is here to ensure a PERFECT CRIMPED JOINT always as a JOINT can be considered as the NERVE CENTRE of an Electrical System.

The most commonly used Crimping methods are Indent style and Hexagonal type. Indent style crimping method is usually used for crimping fine stranded and compacted conductors. This style of crimp yields great pullout resistance and good electrical performance when correctly made with a properly sized tool for the cable and connector. As the strands are formed tightly together inside the connector, nearly all air gaps are removed from the conductor. However, it is more difficult to check if an indent style crimp has been properly made compared to hex-style crimps.

Hexagonal type the most common type of crimp, create strong mechanical connections. The advantage of this style crimp is that force is applied consistently from all directions over a larger area during crimping, preventing any damage to the conductors. This style crimp is an industry standard for aluminum and copper cables up to 1000mm2. Hex-style crimps yield superior electrical performance in addition to great pullout strength.



**Indent Crimp Profile** 




**Hexagonal Crimp Profile** 


### **QUICK REFERENCE WHICH TELLS YOU THE CRIMP QUALITY**



Acceptable



Not Acceptable-under Crimped



Not Acceptable-over Crimped





# MANUAL HAND CRIMPING TOOL

Model No. CT-MC-120



Crimping Profile

Length: 650 mm Weight: 3.5 kgs

**Technical Data:**Max Output : 4 tons





From 10 Sq.mm. to 120 Sq.mm. Ring profile dies provided.

#### Features:

Forged Jaws ensure longlife.

Fibre glass handles ensure operator comfort.









MANUAL HAND CRIMPING TOOL

Model No. CT-MC-50





Length: 400 mm Weight: 1.2 kgs

## **Crimping Capacity:**

4 Models available 6 to 50 Sq.mm. 16 to 95 Sq.mm. 6 to 120 Sq.mm. 25 to 150 Sq.mm.





#### Features:

Light weight body. Rotating Hexagonal dies.



